

MATERIAL SAFETY DATA SHEET

Prepared according to the Decree of European Council no. 1907/2006 from 18.12.2006 regarding registering, evaluation, certification and authorizations in range of chemicals (REACH), creation of European Chemicals Agency, changing Directive 1999/45/EC and cancelling decree of Council no. 793/93 and decree of Commission no.1488/94, as well as directives 76/769/EC, 91/155/EC, 93/67/EC, 93/105/EC and 2000/21/EC.

SECTION 1 IDENTIFICATION OF THE PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier:

INTER TROTON SPRAY CYNK- ALU

1.2. Relevant identified uses of the substance or mixture and uses advised against:

Professional repairs of car body repairs.

1.3. Details of the supplier of the safety data sheet:

Manufacturer/Distributor

TROTON Sp. z. o. o.

78-120 Gościno

Ząbrowo, 14A, Poland

Tel./Fax: + 48 94 35 126 22

Tel.: + 48 94 35 123 94

E-mail: troton@troton.com.pl

1.3.1. Responsible person; E-mail: troton@troton.com.pl

1.4. Emergency telephone number: + 48 94 35 126 22 (from 8:00 am – 4:00 pm)

SECTION 2 IDENTIFICATION OF THREATS

2.1. Classification of the substance or mixture

Classification according to Directive 67/548/EEC or Directive 1999/45/EC:

Extremely flammable (F+) (R12).

Irritating (Xi). May cause sensitization by skin contact (R43).

Repeated exposure may cause skin dryness or cracking (R66). Vapours may cause drowsiness and dizziness (R67).

Classification according to Regulation (EC) No 1272/2008:

Flam. Gas 1

Eye Irrit. 2

STOT SE 3

Aquatic Chronic 1



DANGER!

H-phrases:

H220 – Extremely flammable gas

H319 Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H411- Toxic to aquatic life with long lasting

P-phrases:

P210 – Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P273 - Avoid release to the environment.

P405 - Store locked up.

P304 + P341 – IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

2.2. Label elements



Irritating (Xi)

Risk phrases:



Extremely flammable (F+)



Dangerous for the environment (N)

R36 Działa drażniąco na oczy

R66 Repeated exposure may cause skin dryness or cracking

R67 Vapours may cause drowsiness and dizziness

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Safety phrases:

S2 Keep out of the reach of children

S23 Do not breathe gas/spray

S25 Avoid contact with eyes

S26 Keep away from sources of ignition - No smoking

S38 In case of insufficient ventilation, wear suitable respiratory equipment

S51 Use only in well-ventilated areas

EU limit value for this product (IIB(e)) 840 g/l (2010).

VOC = 634,9 g/l

2004/42/WE IIB(e) (840) 634,9

2.3. Information concerning particular hazards for human and environment:

Inhalation: in mild cases it causes cough, irritation of the mouth and throat, sometimes it causes chest pain. In more acute cases it causes headache, vertigo, fatigue, maysthenia, drowsiness and in extreme cases loss of consciousness.

Eye contact: causes mechanical irritation, redness, pain and asthenopia. If the drops of the product get in the eyes, may cause impairment of sight and allergic reactions.

Skin contact: may cause irritation. In case of problematic skin, skin absorption may occur. In case of long term or repeated contact the skin drying and erythroderma may occur. Irritation and redness may occur.

Chronic exposure:

In case of chronic inhalation of the vapour/dust of the product, chest pain, irritation of the mucous membranes, headache, vertigo, excitement or drowsiness, problems with the digestive system, exsiccation, cracking of the skin and allergy may occur.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Mixture:

Description	EEC No	CAS No	EU No	(%)	Classification			
					REACH		CLP	
					Hazard symbol	R phrase	Hazard cat.	H phrase
Acetone	606-001-00-8	67-64-1	200-662-2	25-50	F Xi	R11 R36 R66 R67	Flam. Liq. 2 Eye Irrit. 2 STOT SE 3	H225 H319 H336
Butane	601-004-00-0	106-97-8	203-448-7	10-25	F+	R12	Flam. Gas 1 Press. Gas	H220
Propane	601-003-00-5	74-98-6	200-827-9	10-25	F+	R12	Flam. Gas 1 Press. Gas	H220
Solvent naphtha (petroleum), light arom.**,***	649-356-00-4	64742-95-6	265-199-0	2,5-10	Carc. Cat. 2; R45 Xn; R65	Xn;Xi; N R10-37- 51/53-65- 66-67	Carc. 1B Asp. Tox. 1	H350 H304
Zinc	030-001-00-1	7440-66-6	231-175-3	1-2,5	F N	R15-17 R50-53	Water-react. 1 Pyr. Sol. 1 Aquatic Acute1 Aquatic Chronic 1	H260 H250 H400 H410
Aluminium	013-001-00-6	7429-90-5	231-072-3	1-2,5	F	R15-17	Water -react 2 Flam. sol.1	H261 H228
Butan-1-ol	603-004-00-6	71-36-3	200-751-6	1-2,5	Xn Xi	R10 R22 R37/38- 41 R67	Flam. Liq. 3 Acute Tox. 4 STOT SE 3 Skin Irrit. 2 Eye Dam. 1 STOT SE 3	H226 H302 H335 H315 H318 H336
Trizinc bis(orthophosphate)	030-11-00-6	7779-90-0	231-944-3	0,1-1	N	R50-53	Aquatic Acute1 Aquatic Chronic1	H400 H410

Full meaning of phrases and symbols are in section 16.

SECTION 4 FIRST AID MEASURES

4.1. Description of first aid measures:

Take normal precautionary measures applied during the handling of chemicals. In case of any symptoms, seek medical advice.

IN CASE OF INGESTION:

Measures:

- If swallowed, do not induce vomiting (risk of aspiration).
- Obtain immediate medical help.

IN CASE OF INHALATION:

Measures:

- Remove the affected person to fresh air, keep calm, cover with a blanket.
- In case of shortness of breath, give oxygen.
- If breathing has stopped, administer artificial respiration and obtain medical help.

IN CASE OF SKIN CONTACT:

Measures:

- Immediately flush with plenty of water.
- Take off all contaminated clothing.
- Wash skin with plenty of water and soap.
- In case of symptoms, obtain medical attention and show him the label!

IN CASE OF EYE CONTACT:

Measures:

- Remove contact lenses.
- Flush immediately with plenty of water for 15 minutes, holding the eyelids wide open.
- Consult an ophthalmologist.

4.2. Most important symptoms and effects, both acute and delayed:

Inhalation: in mild cases it causes cough, irritation of the mouth and throat, sometimes it causes chest pain. In more acute cases it causes headache, vertigo, fatigue, maysthenia, drowsiness and in extreme cases loss of consciousness.

Eye contact: causes mechanical irritation, redness, pain and asthenopia. If the drops of the product get in the eyes, may cause impairment of sight and allergic reactions.

Skin contact: may cause irritation. In case of problematic skin, skin absorption may occur. In case of long term or repeated contact the skin drying and erythroderma may occur. Irritation and redness may occur.

Chronic exposure:

In case of chronic inhalation of the vapour/dust of the product, chest pain, irritation of the mucous membranes, headache, vertigo, excitement or drowsiness, problems with the digestive system, exsiccation, cracking of the skin and allergy may occur.

4.3. Indication of any immediate medical attention and special treatment needed:

No special antidote, apply symptomatic treatment.

SECTION 5 FIRE-FIGHTING MEASURES

5.1. Extinguishing media:

5.1.1. Suitable extinguishing media:

Foam, carbon dioxide or dry chemical.

5.1.2. Unsuitable extinguishing media:

Strong water jet.

5.2. Special hazards arising from the substance or mixture:

In case of combustion, carbon oxide and toxic fumes are formed.

5.3. Advice for firefighters:

Wear full protective clothing (gas-tight and antistatic) and self-contained breathing apparatus.

Cool the fire affected containers with water spray.

Prevent penetration into ground and surface water. Prevent penetration of the fire extinguishing media into ground and surface water. Collect fire extinguishing media separately, do not discharge into sewage system.

SECTION 6 ACCIDENTAL RELEASE MEASURES

- 6.1. Personal precautions, protective equipment and emergency procedures:
- 6.1.1 For non-emergency personnel:
Keep unprotected people away, allow only well trained experts wearing suitable protective clothing to abide in the field of accident.
- 6.1.2. For emergency responders:
Remove all ignition sources, flames.
Protect sewage outlets.
Disperse vapours with water spray.
Stop leakage – close the source of the leakage, seal damaged container and place in an other container.
Ensure adequate ventilation.
Wear protective clothing and gloves.
Do not inhale vapours.
- 6.2. Enivornmental precautions:
Dispose of spillage and waste (product/packaging) in accordance with all applicable environmental laws. Do not allow to enter sewers/soil/surface or ground water. Notify the respective authorities in accordance with local law in the case of environmental pollution immediately.
- 6.3. Methods and material for containment and cleaning up:
Absorb the spilled product with an inert substance (e.g.: sand or diatomaceous earth) and transfer into a sealed container, and send to an authorized waste disposal company. During disposal wear suitable personal protective equipment.
- 6.4. Reference to other sections:
For further and detailed information see section 8 and 13.

SECTION 7 HANDLING AND STORAGE

- 7.1. Precautions for safe handling:
Observe conventional hygiene precautions.
Avoid contact with skin and eyes.
Do not inhale vapours.
Do not eat, drink or smoke during the usage.
Technical measures:
Use only in well-ventilated places with exhaust ventilation.
Tools, equipments and containers must be sealed tightly.
Precautions against fire and explosion:
Keep away from heat and ignition sources.
- 7.2. Conditions for safe storage, including any incompatibilities:
Technical measures and storage condition:
Keep in original, tightly closed and labelled container.
The place of storage has to be properly ventilated and cleanable.
Store in cool and dry place.
Protect against sunlight.
Store below 20°C.
Do not store with self-igniting substances and peroxides.
Store in original, properly labelled containers, which are tightly sealed.
Do not smoke, eat, use open fire and sparking tools in the place of the storage.
Keep away from the reach of children.
Follow all instructions on the label.
Incompatible materials: strong oxidizing agents.
Packaging material: original container.
- 7.3. Specific end use(s):
No specific instructions available.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1. Control parameters:

Substance name	CAS Nr.	8 hours	Short term
Xylene	1330-20-7	221 mg/m ³ , 50 ppm	442mg/m ³ , 100 ppm

8.2. Exposure controls:

In case of a hazardous material with no controlled concentration limit it is the employer's duty to keep concentration levels down to a minimum achievable by existing scientific and technological means, where the hazardous substance poses no harm to workers.

8.2.1 Appropriate engineering controls

In pursuance of work is proper foresight needed to avoid spilling onto clothes and floors and to avoid contact with eyes and skin.

The suction of the vapours at the source(s) of emission and general exhaust ventilation is required. The exhaust vents should be placed in the upper part of the room and at the floor level.

Keep away from heat and ignition sources.

8.2.2. Individual protection measures, such as personal protective equipment:

1. Eye/face protection: use adequate protective goggles.

2. Skin protection:

a. Hand protection: use impervious gloves.

b. Other: use impervious protective clothes.

3. Respiratory protection: if exposure is likely to exceed the occupational exposure, use approved respiratory protective equipment.

4. Thermal hazard: None known.

8.2.3. Environmental exposure controls:

No specific prescription.

The requirements detailed in Section 8 assume skilled work under normal conditions and usage of the product for appropriate aims. If conditions differ from normal or work is carried out under extreme conditions an expert's advice should be sought out before deciding upon further protective measures.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES:

9.1. Information on basic physical and chemical properties

Physical condition/form colour	Brayt metallic aerosol
Odour	typical of solvents
Boiling point	98°C
Flesh point:	Not data
Melting point	No data
Vapours pressure	8300 hPa
Solubility in water and other solvents	Very weak
Solubility in organic solvents	No data
Specific gravity	No data
pH:	No data
Ignition temperature	395 °C
Explosive properties: limits	Lower 1,5 vol% upper 13,0 vol%
Autoignition point	235 °C
Flammable	Extremely flammable
Oxidizing properties	Not oxidizing, no concern
Distribution ratio 1-n-octanol/water	No data available
Other properties:viscosity	No data available

9.2. Other information:

Organic solvent content: 89,3%

Denisty : 0,71g/cm³

SECTION 10 STABILITY AND REACTIVITY10.1. Reactivity:

None known.

10.2. Chemical stability:

At normal temperature: stabile at general conditions of work.

10.3. Possibility of hazardous reactions:

None known.

10.4. Conditions to avoid:

High temperature, fire.

- 10.5. Incompatible materials:
storing oxidizing agents.
- 10.6. Hazardous decomposition products:
In case of high temperature or fire, carbon oxides and toxic smoke may evolve.

SECTION 11 TOXICOLOGICAL INFORMATION

- 11.1. Information on toxicological effects:
Acute toxicity: Harmful by inhalation and in contact with skin.
Irritation: None known.
Corrosivity: None known.
Sensitisation: None known.
Repeated dose toxicity: Repeated exposure may cause skin dryness or cracking.
Carcinogenicity: None known.
Mutagenicity: None known.
Reproduction toxicity: None known.
- 11.1.1. For substances subject to registration, brief summaries of the information derived from the test conducted:
No data available.
- 11.1.2. Relevant toxicological properties of the hazardous substances:
Information on toxicological effects:

<i>Substance</i>	<i>CAS-nr</i>	<i>Method</i>	<i>Value</i>	<i>Unite</i>
Solvent naphtha (petroleum), light arom	64742-95-6	LD50(oral, rat)	3,9	g/kg
		LD50(dermal, rabbit)	>3	g/kg
		LC50(inhalation, rat)	>14,4	mg/l/4h
Acetone	67-64-1	LD50(oral, rat)	5800	mg/kg
		LD50 (dermal, rat)	20000	mg/m ³ /4h
Pentane	109-66-0	LD50(oral, rat)	>16000	mg/g
		LD ₅₀ (dermal, rat):	>2500	mg/kg
		LD50 (dermal, rabbit):	>5000	mg/kg
		LC50 (dermal, rat):	>100	mg/ m ³ /4h
Butane	106-97-8	LD50(rat)	658	mg/ m ³ /4h

- 11.1.3. Information on likely routes of exposure:
ingestion, inhalation, skin and eye contact.
- 11.1.4. Symptoms related to the physical, chemical and toxicological characteristics:
Inhalation: in mild cases it causes cough, irritation of the mouth and throat, sometimes it causes chest pain. In more acute cases it causes headache, vertigo, fatigue, maysthenia, drowsiness and in extreme cases loss of consciousness.
Eye contact: causes mechanical irritation, redness, pain and asthenopia. If the drops of the product get in the eyes, may cause impairment of sight and allergic reactions.
Skin contact: may cause irritation. In case of problematic skin, skin absorption may occur. In case of long term or repeated contact the skin drying and erythroderma may occur. Irritation and redness may occur.
Chronic exposure:
In case of chronic inhalation of the vapour/dust of the product, chest pain, irritation of the mucous membranes, headache, vertigo, excitement or drowsiness, problems with the digestive system, exsiccation, cracking of the skin and allergy may occur.
- 11.1.5. Delayed and immediate effects as well as chronic effects from short and long-term exposure:
Harmful by inhalation and in contact with skin.
Repeated exposure may cause skin dryness or cracking.
- 11.1.6. Interactive effects:
No data available.
- 11.1.7. Absence of specific data:
No information.
- 11.1.8. Other information:
No data available.

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity:

Aquatic toxicity:

<i>Substance:</i>	<i>CAS-number:</i>	<i>Method:</i>	<i>Value:</i>	<i>Unit:</i>
<i>Aceton</i>	67-64-1	LC50-fish (<i>Leuciscus idus melanotus</i>)	7505-11300	mg/l (48h)
		LC50-fish (<i>Salmo gairdneri</i>)	6100	mg/l (24h)
		LC50-fish (<i>Poecilla reticulata</i>)	6363	mg/l (14dni)
		LC50-fish (<i>Alburnus alburnus</i>)	11000	mg/l (96h)
		LC50-invertebrata (<i>Daphnia magna</i>)	>10000	mg/l (24h)
		EC50-algae (<i>Anabaena cylindrica</i>) 2	844	mg/l(14dni)
		EC50-bacterium (<i>Photobacterium phosphoreum</i>)	14500	mg/l(15min)

Effect on activated sludge: at proper entering of small concentrations to biological sewage treatment plants no perturbations should be expected during the decomposition of the activated sludge.

12.2. Persistence and degradability:

No data available.

12.3. Bioaccumulation potential:

No data available.

12.4. Mobility in soil:

No data available.

12.5. Results of PBT and vPvB assessment:

No data available.

12.6. Other adverse effects:

No data available.

SECTION 13 DISPOSAL CONSIDERATIONS13.1. Waste treatment methods:

Disposal according to the local regulations.

13.1.1. Information regarding the disposal of the product:

Do not dispose with communal wastes, do not pour into drainage system. Incinerate in specially adapted installations or deliver to authorized waste collector.

European Waste Catalogue code:

16 05 04* gases in pressure containers (including halons) containing dangerous substances

* hazardous waste.

13.1.2. Information regarding the disposal of the packaging

Used packaging should be delivered to authorized collector who has due permission within the range of waste management and especially in dangerous waste management.

European Waste Catalogue code:

For used packaging:

15 01 10* packaging containing residues of or contaminated by dangerous substances

* hazardous waste.

13.1.3. Physical/chemical properties that may affect waste treatment options shall be specified:

None known.

13.1.4. Sewage disposal:

None known.

13.1.5. Special precautions for any recommended waste treatment:

No data available.

SECTION 14 TRANSPORT INFORMATION**Land transport (ADR/RID)**

UN Number

UN1950




UN proper shipping name

AEROSOLS, flammable

Transport hazard class(es)

2.1

Label: 2

		
Packing group		Not applicable
Environmental hazards		YES see 5.2.1.8 Agreement ADR
Tunnel restriction code		D
Marine transport IMDG/IMO		
UN Number		UN1950
UN proper shipping name		AEROSOLS, flammable
Transport hazard class(es)		2.1 Label: 2
		
EmS code		F-D, S-U
Packing group		Not applicable
Environmental hazards		YES 5.2.1.6 IMDG Code
Air transport IATA		
UN Number		UN1950
UN proper shipping name		AEROSOLS, flammable
Transport hazard class(es)		2.1 Label: 2
		
Packing group		Not applicable
Environmental hazards		YES 7.1.7 IATA Dangerous Goods Regulation

SECTION 15 REGULATORY INFORMATION

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture:
 REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC
 COMMISSION REGULATION (EC) No 790/2009 of 10 August 2009 amending, for the purposes of its adaptation to technical and scientific progress, Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures
 DIRECTIVE 1999/45/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 May 1999 concerning the approximation of the laws, regulations and administrative provisions of the Member States relating to the classification, packaging and labelling of dangerous preparations
 REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006
 COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
- 15.2. Chemical safety assessment: -

SECTION 16 OTHER INFORMATION

Information regarding the revision of the safety data sheet: -
 Full text of the abbreviations in the safety data sheet:
 DNEL: Derived no effect level. PNEC: Predicted no effect concentration. CMR effects: carcinogenicity, mutagenicity and toxicity for reproduction: PBT: Persistent, bioaccumulative and toxic. . n.d.: not defined. . n.a.: Not applicable. .
 Data sources: -
 Relevant R-Phrases (number and full text) of Section 2 and 3:
 R10 Flammable
 R11 Highly flammable

- R12 Extremely flammable
 R15 Contact with water liberates extremely flammable gases
 R17 Spontaneously flammable in air
 R22 Harmful if swallowed
 R36 Irritating to eyes
 R37 Irritating to respiratory system
 R37/38 Irritating to skin
 R41 Risk of serious damage to eyes
 R45 May cause cancer
 R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
 R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
 R65 Harmful: may cause lung damage if swallowed
 R66 Repeated exposure may cause skin dryness or cracking
 R67 Vapours may cause drowsiness and dizziness
- Relevant H-Phrases (number and full text) of Section 2 and 3:
- Acute Tox. 4 Acute toxicity, category 4
 Aquatic Acute 1 Hazardous to the aquatic environment, category 1
 Aquatic Chronic 1 Hazardous to the aquatic environment, category 1
 Asp. Tox. 1 Aspiration hazard, category 1
 Carc. 1B Carcinogenicity, category 1
 Eye Dam. 1 Serious eye damage/eye irritation, category 1
 Eye Irrit. 2 Serious eye damage/eye irritation, category 1
 Flam gas 1 Flammable gas, category 1
 Flam. Liq. 2 Flammable liquid, category 2
 Flam. Liq. 3 Flammable liquid, category 3
 Flam. sol.1 Flammable solid, category 1
 Press gas 1 Gases under pressure, category 1
 Pyr. Sol. 1 Pyrophoric solid, category 1
 Skin Irrit. 2 Skin corrosion/irritation, category 1
 STOT SE 3 Specific target organ toxicity — single exposure, category 3
 Water –react 2 Substance or mixture which in contact with water emits flammable gas, category 2
 Water-react. 1 Substance or mixture which in contact with water emits flammable gas, category 1

- H220 Extremely flammable gas
 H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H228 Substancja stała łatwopalna.
 H261 In contact with water releases flammable gases.
 H250 Catches fire spontaneously if exposed to air.
 H260 In contact with water releases flammable gases which may ignite spontaneously.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.

Training instructions: -

Recommended restrictions on use (non-statutory recommendations by supplier): -

This safety data sheet had been prepared on the basis of information provided by the manufacturer. The information, data and recommendations contained herein are provided in good faith, obtained from reliable sources and believed to be true and accurate as of the date issued; however, no representation is made as to the comprehensiveness of the information. The MSDS shall be used only as a guide for handling the product; in the course of handling and using the product other considerations may arise or be required. Since the conditions or the handling, the storage and the disposal of this product are beyond the control of the manufacturer, the distributor or the preparer of this SDS, no warranty, expressed or implied, regarding the product described in this MSDS shall be created or inferred by any

statement in this SDS. No responsibility is assumed regarding the accuracy, completeness or suitability of all or any of the information contained herein or the results to be obtained from the use thereof at the time of use. In no way shall the manufacturer, the distributor or the preparer of the be liable for any claims, losses or damages of third parties, personal injury, property damage, lost profits or any special, direct, indirect, incidental, consequential or exemplary damages resulting from the use of or reliance upon such information. Users are cautioned to determine the appropriateness and applicability of the above information to their particular circumstances and purposes and assume all risk associated with the use of this product. It is the responsibility of the user to fully comply with local, national and international regulations concerning the use of this product.